



# PERFORMANCE NOTEBOOK

## Cape Horn 34XS



BOAT		ENGINE		OTHER SPECS	
<b>34XS</b>		<b>Quad Suzuki DF350ATX</b>		<b>Propeller</b>	
Material:	Fiberglass	Engine Type:	4-Stroke 6Cyl.	Material:	Stainless
Length:	34' 11"	HP:	350	Diameter/Pitch:	15.5 X 25.5
Beam:	9' 3"	Displacement:	267.9cu. In.	Number of Blades:	Twin 3 Blade
Weight:	8000 lb.s	Operating Range:	5700-6300	<b>Mounting Height</b>	
Maximum HP:	900	Weight:	727 lb.s	Hole Position:	#3 Hole
Fuel Capacity:	275 gallons	Lubrication:	Wet Sump	Jack Plate:	NA
Transom Height:	25"	Fuel Delivery:	Multi-Point EFI		
Steering:	Hydraulic	Ignition:	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
<b>RPM</b>	<b>MPH</b>	<b>GPH</b>	<b>MPG</b>	<b>RANGE</b>	Water Conditions:	1-2' Chop
IDLE	4.1	1.1	3.68	911	Wind Velocity:	5-10mph
1000	6.2	2.4	2.62	648	Air Temperature:	80 F
1500	8.3	4.5	1.85	459	Fuel Load:	270 gal.
2000	9.5	6.9	1.38	341	Weight Onboard:	2 person/FSG*
2500	16.5	11.5	1.43	354		
3000	26.1	16.0	1.64	405		*Full Safety Gear
3500	32.8	22.0	1.49	368	<b>PERFORMANCE SUMMARY</b>	
4000	38.8	26.6	1.46	361	Top Speed	58.6 MPH
4500	43.4	32.1	1.35	335	0-25 Acceleration	7.94 Seconds
5000	49.6	41.1	1.21	299	Optimum Cruising	3000 RPM
5500	55.2	49.6	1.11	275	Range	405 Miles
5900	58.6	57.6	1.02	252	Best Cruising	3000 RPM
					Fuel Efficiency	1.64 MPG

Results may vary. Range based on 90% fuel capacity.

### FOR MORE INFORMATION CONTACT:

Fabbro Marine Group - Milton, FL  
[www.capehornboats.com](http://www.capehornboats.com)  
 (850) 626-2211

SUZUKI MARINE USA LLC - Tampa, FL  
[www.suzukimarine.com](http://www.suzukimarine.com)  
 (813)687-7200